

Claims.

1-13. (canceled)

14.(currently amended) A connection according to claim ~~13~~ 24, wherein the actuator is a motor.

15.(currently amended) A connection according to claim ~~13~~ 24, wherein the actuator is connected to an impact sensor capable of identifying contact between the bodywork and a pedestrian.

16-20. (canceled)

21.(currently amended) A connection according to claim ~~20~~ 32, wherein the fusible fastener comprises an insert selected from the group consisting of an overmolded insert or a crimped insert.

22-23. (canceled)

24.(new) A connection for use in a motor vehicle having bodywork adapted for receiving an impact, the motor vehicle comprising a plurality of side rails and a structural part supporting the bodywork, the structural part comprising a top edge situated near a zone of the bodywork that might be impacted by a head or hip of a pedestrian, the connection comprising a collapsible force-opposing member that enables the side rail to oppose a vertical force and that comprises a finger mounted on each side rail, an actuator capable of moving the finger between an extended position in which the finger retains the structural part vertically, and a retracted position in which the structural part is released; and an actuator capable of moving the finger between an

extended position in the which the finger retains the structural part vertically and a retracted position in which the structural part is released.

- 25.(new) A connection according to claim 24, wherein the motor vehicle comprises a front face and the front face comprises the structural part, and the structural part includes a cooling unit.
- 26.(new) A connection for use in a motor vehicle having bodywork adapted for receiving an impact, the motor vehicle including a side rail and a structural part supporting the bodywork, the structural part comprising a fusible portion and a top edge situated near a zone of the bodywork that might be impacted by a head or hip of a pedestrian, the connection comprising a collapsible force-opposing member that enables the side rail to oppose a vertical force and the force-opposing member comprising the fusible portion of the structural part.
- 27.(new) A connection according to claim 26, wherein the motor vehicle comprises a front face and the front face comprises the structural part, and the structural part includes a cooling unit.
- 28.(new) A connection for use in a motor vehicle having bodywork adapted for receiving an impact, the connection comprising a side rail and a structural part supporting the bodywork, the structural part comprising a top edge situated near a zone of the bodywork that might be impacted by a head or hip of a pedestrian, the connection comprising a collapsible force-opposing member that enables the side rail to oppose a vertical force, the force-opposing member comprising an insert embedded in the

structural part and fixed to the side rail, the insert adapted to split the structural part when subjected to vertical force above a predetermined threshold.

- 29.(new) A connection according to claim 28, wherein the motor vehicle comprises a front face and the front face comprises the structural part, and the structural part includes a cooling unit.
30. (new) A connection for use in a motor vehicle having bodywork adapted for receiving an impact, the connection comprising a side rail and a structural part supporting the bodywork, the structural part comprising a hood lock and a top edge situated near a zone of the bodywork that might be impacted by a head or hip of a pedestrian, the connection comprising a collapsible force-opposing member that enables the side rail to oppose a vertical force, and a sensor capable of releasing the hood lock when the bodywork impacts a pedestrian.
- 31.(new) A connection according to claim 30, wherein the motor vehicle comprises a front face and the front face comprises the structural part, and the structural part includes a cooling unit.
- 32.(new) A connection for use in a motor vehicle having bodywork adapted for receiving an impact, the motor vehicle comprising a side rail, fender linings comprising a bottom, and a structural part supporting the bodywork and comprising a top edge and a plurality of ends, the top edge situated near a zone of the bodywork that might be impacted by a head or hip of a pedestrian, and the ends extending beneath the bottom of the fender linings, the connection comprising a collapsible force-

opposing member that enables the side rail to oppose a vertical force; and at least one fusible fastener securing each end of the structural part to the fender lining.

33.(new) A connection according to claim 32, wherein the motor vehicle comprises a front face and the front face comprises the structural part, and the structural part includes a cooling unit.